



INSTALLATION INSTRUCTIONS

Accessory
ALL SEASON RUBBER
FLOOR MATS


Application
2009 ELEMENT
(DOG FRIENDLY PACKAGE)

Publications No.
All 43057
Issue Date
NOV 2009


Put this information in the glove box with the vehicle owner's manual.

PARTS LIST

Front mat



Rear mat



3 Front floor mat anchors




3 Self-tapping screws



Washer-screw



Rear floor mat anchor



TOOLS AND SUPPLIES REQUIRED

Phillips screwdriver

Utility knife

Tape measure

Drill

Electrical tape

3 mm and 6 mm Drill bits

Eye protection (face shield, safety goggles, etc.)

File

INSTALLATION

Customer Information: The information in this installation instruction is intended for use only by skilled technicians who have the proper tools, equipment, and training to correctly and safely add equipment to your vehicle. These procedures should not be attempted by "do-it-yourselfers."

NOTE:

- A floor mat anchor prevents the front mat from sliding forward and possibly interfering with the pedals.
- If you remove the front mat, make sure you re-anchor it when you put it back in your vehicle.
- If you replace the floor mat, use factory floor mats designed to be used with the floor mat anchor.
- If you use a non-factory floor mat in the driver's foot well, make sure it fits properly, and that it can be used with the floor mat anchor.
- Do not put additional floor mats on top of the anchored mat, otherwise the additional mats may slide forward and possibly interfere with the pedals.